

MV MINI NEEDLE VALVE

SPECIFICATIONS

RATED TO 6,000 PSI

CARBON STEEL CONSTRUCTION

STAINLESS STEEL CONSTRUCTION

VITON PACKING AND SEALS

WORKING TEMPERATURE -20 DEG F TO 100 DEG F

THREADS CONFORM TO ASME B1.20.1



MVD

MATERIAL

Description	Grade/ASTM Specification	
	Body Material	
1 Body	Carbon Steel	SS316
2 Stem	SS304	SS316
3 Bonnet	Carbon Steel	SS316
4 Handle	Carbon Steel	SS316



MVH

PART NUMBERS

No.	DIMENSION	STYLE	WEIGHT
MVDS4	1/4"	FXF	0.66
MVDS5	1/4"	MXM	0.66
MVDS6	1/4"	MXF	0.66
MVDC4	1/4"	FXF	0.66
MVDC5	1/4"	MXM	0.66
MVDC6	1/4"	MXF	0.66

PART NUMBERS

No.	DIMENSION	STYLE	WEIGHT
MVHS4	1/4"	FXF	0.71
MVHS5	1/4"	MXM	0.71
MVHS6	1/4"	MXF	0.71
MVHC4	1/4"	FXF	0.71
MVHC5	1/4"	MXM	0.71
MVHC6	1/4"	MXF	0.71

ORDERING INFORMATION

